


ICC Cable

ICC5/x

Art. 71.60.40xx



ws : wit	blanc	weiss	white
br : bruin	brun	braun	brown
gn : groen	vert	grun	green
ge : geel	jaune	gelb	yellow
gr : grijs	gris	grau	grey
rs : roos	rose	rosa	pink
bl : blauw	bleu	blau	blue
rt : rood	rouge	rot	red
sw : zwart	noir	schwarz	black
vl : paars	violet	violet	violet
be : beige	beige	beige	tan
or : oranje	orange	orange	orange

TOP VIEW CONNECTOR:			
pair	color code	T568B	pin
1	ws-bl	5	1 ws-or
	bl	4	2 or
2	ws-or	1	3 ws-gn
	or	2	4 bl
3	ws-gn	3	5 ws-bl
	gn	6	6 gn
4	ws-br	7	7 ws-br
	br	8	8 br

Terminal N°1 is the terminal to the extreme left as you face the cable opening, latch tab down.

Specifications

Size of conductors	24AWG (7x0.20 ± 0.005mm) stranded copper wire
diameter of dielectric	0.95± 0.03mm
Number of twist pairs	Four pairs
Plug	Modular U.S. shielded type 10P10C
jacket material	LSZH
Part Number	71.60.4002 (2 meter) 71.60.4005 (5 meter) 71.60.4010 (10 meter) 71.60.4020 (20 meter)